





Permanent Mount

Single Edge Mount

Single Multi-Mount 10-16 Vdc 10-30 Vdc ECE R65/EMC Xylex Lens (amber, bue or red)

Black Housing #EGHST1(x)-12 #EGHST1(x) #EGHSTE1(x)B #EGHSTE1(x)B-EU
White Housing #EGHST1(x)W-12 #EGHST1(x)W #EGHSTE1(x)W #EGHSTE1(x)W-EU

Includes three mounting options: Permanent, Edge and 3M Adhesive Mount

Dual Multi-Mount10-16 Vdc10-30 VdcBlack Housing#EGHDT1(xx)-12#EGHDT1(xx)White Housing#EGHDT1(xx)W-12#EGHDT1(xx)W

Includes three mounting options: Permanent, Dual Edge and 3M Adhesive Mount

Single Stop/Tail Multi-Mount 10-16 Vdc
Black Housing #EGHSTTR
White Housing #EGHSTTRW

Includes two mounting options: Permanent and 3M Adhesive Mount

REPLACE (x) IN ORDER NUMBER FOR COLOR SELECTION Solid Colors = A B G R W Dual/Split Colors = A B D E F G H J K L M N P R W

Features

- · Sleek, narrow surface mount light, fits almost anywhere
- · Premium optics offer optimal power and brightness
- Red Stop/Tail model is a low power, steady-on red running light once brake is applied, light flashes 5 times and remains on at full power while brake is activated
- Includes 18" of 3-wire cable
- · Rock Light offers an anti-crush, super duty bracket for the most demanding applications and environments
- Extreme duty Rock Bracket offers up to 30 degrees of light head adjustability to angle light







Rock Light

Rock Light
Warning
Stop/Tail

10-16 Vdc #EGHST3(x)-12 10-30 Vdc #EGHST3(x) #EGHSTT3R



For other GHOST products, refer to the Surface Mounts on page 37 and the Recess Mount on page 57.

TECHNICAL SPECIFICATIONS

FLASH PATTERNS	33 flash patterns
LIGHT SYNC	Yes
LED COUNT	6 LEDs
INPUT VOLTAGE	10-16 Vdc or 10-30 Vdc
CURRENT DRAW	< 0.75 Amps per module @ 12.8 Vdc
OPERATING TEMPERATURE	-40° C to +65° C / -40° F to +149° F
DIMENSIONS	Multi: 4" (10 cm) L x 0.9" (2.3 cm) H x 1.8" (4.6 cm) D
	Rock: 4.8" (12 cm) L x 2" (5.1 cm) H x 1.6" (4.1 cm) D
MOUNTING	Multi: Permanent, Edge or Adhesive mount
	Stop Tail: Permanent or Adhesive mount
CERTIFICATIONS	SAE J595, Class 1 certified; CA Title 13: Article 22 compliant; EMC certified, 72/245/EEC and
	ECE 65, Category X, Class 1 certified
WARRANTY	Five-year